

582U



Product description

TransferRite® Ultra™ 582U is a medium tack application tape featuring a unique rubber-based adhesive system equipped with a special adhesive promotor that provides superior adhesion to liner. Especially designed for use over ready-to-apply graphics or where large areas of exposed liner are present.

Performance features

- Increased Quick-Stick: saves time
- Terrific lay-flat: reduces wrinkling, tunneling and edge lifting
- Ultra Adhesive: greater adhesion to liner and no haze
- Cost effective: trouble-free stacking and storage
- Affordable: very good value for money

Applications

Can be used in sign shops for small one piece decals and mid-sized line striping. 582U is best used for lettering from 5cm up to 31cm.

Technical information

Paper thickness (without adhesive)	83 µm
Adhesive thickness	23 µm
Total thickness	106 µm
Adhesive type	natural rubber latex with adhesive promotor
Adhesive strength (adhesion to steel)	3 N/25mm (medium tack)
Core colour	yellow
Tensile strength	88 N/25mm
Elongation at break	3%
Shelf life (from time of manufacture)	30 months (21 °C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

