

592U



Product description

TransferRite® Ultra™ 592U is a high tack application tape featuring a unique rubber-based adhesive system equipped with a special adhesive promotor that provides superior adhesion to liner. Especially designed for use over ready-to-apply graphics or where large areas of exposed liner are present.

Performance features

- Increased Quick-Stick: saves time
- Terrific lay-flat: reduces wrinkling, tunneling and edge lifting
- Ultra Adhesive: greater adhesion to liner and no haze
- Cost effective: trouble-free stacking and storage
- Affordable: very good value for money

Applications

Can be used in sign shops for decals and lettering smaller than 5cm and fine line striping. 592U can also be used for 4-colour process printing, on smooth top-coated decals and thermal die-cuts.

Technical information

Paper thickness (without adhesive)	83 µm
Adhesive thickness	25 µm
Total thickness	108 µm
Adhesive type	natural rubber latex with adhesive promotor
Adhesive strength (adhesion to steel)	4.1 N/25mm (high tack)
Core colour	red
Tensile strength	88 N/25mm
Elongation at break	3%
Shelf life (from time of manufacture)	30 months (21 °C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

