

TECHNICAL DATA SHEET



**Self-adhesive polyester +
liner, 115gsm**

Item	Description	Specification
Fabric structure	Article Code	TAP-1130
	Total Weight	115gsm (±20gsm)
	Total Thickness	290my (±20my)
	Front Layer	Polyester 100%
	Fabric Tenacity (DIN EN ISO 2060)	150D*150D
	Construction (Weaving)	n.a.
	Breaking Tensile Strength DIN 53354	Warp: 480 / Weft: 380
	Tearing Strength DIN 53356	n.a.
Adhesive	Type	Transparent acrylic sensitive glue.
Coating information	Weight of coating (dry)	30gsm
	Printing Surface Finish	Matt
	Colour	White
	Brightness	3,5 (Gardner 60)
	Opacity	65%

Available Sizes	1,27*30m
Applications	Indoor applications for fine art, pop-up, display, sign and light boxes advertising. Outdoor applications: suitable for max. 12 months.
Printability	Digital Printing: Plotters with solvent, eco-solvent, UV curable and latex inks.
	Screen Printing: solvent, eco-solvent, UV curable and water based inks.
	Notes: due to the wide variety of UV inks products and digital printing machines, testing before printing is always recommended.
Storage Period	24 months under ordinary condition at the temperature mean of 22 °C (min. 12 °C, max. 32 °C) and relative humidity of 45 - 65%. The material must stay in its box and does not have to be at sun light, otherwise the coating can be damaged.
Notes	Published information is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of the products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages. All specifications are subject to changes without prior notice.