



TECHNICAL DATA SHEET - FLOORTAC HX3151WT FLOOR & WALL TACK REMOVABLE

Floor & Wall-R is a 150micron textured white PVC laminated with a removable 'structured' clear acrylic adhesive. The PVC is suitable for printing by Latex, UV & most solvent based inks. This product has been developed for use as a digitally printable 'easy apply' wallpaper which is temporarily repositionable and then builds to a strong 'removable' bond when laminated to painted/sized plasterboard walls, smooth plastics & metal surfaces.

Application

Surfaces must be clean and dry and with no loose or badly adhered paint in order to achieve maximum performance. After correct positioning, release paper should be slowly removed whilst air is 'pushed' out through the micro-structured adhesive with the use of a suitable clean, soft non-scratching squeegee or other suitable means. Particular attention should be given to firmly sealing down all PVC edges. Maximum bond strength is normally achieved after 24 hours.

150 TEXTURED WHITE PVC / CLEAR REMOVABLE PSA / 135GSM 'STRUCTURED' KRAFT RELEASE

TYPICAL AVAILABLE WIDTHS:	1370mm
APPLICATION TEMP:	+10°C - +40°C
SERVICE TEMP;	-20°C - +70°C
SHELF LIFE;	1 Year









