

Poli-FLEX NYLON 4800 SERIES

Product Information

Poli-Flex Nylon is a thermally transferable Polyurethane-film, appropriate for lettering on hydrophobic, water-repellent Nylon textiles which are used for working-cloth; sport and leisure wear.

The Transfer film is laminated with a special adhesive on the back side. A transparent Polyester liner guarantees that the Poli-Flex Nylon can be cut with all current plotters.

Application

- Weeded letters are transferred by heat press with medium pressure and at a temperature from 155°C to 165°C during a period of 30-50 sec. The thermal transfer demands a balanced temperature and pressure impact.
- The transparent transferfilm (Polyesterfilm) can carefully be removed either under cold or warm conditions.

Technical Data

- Washable up to +30°C and appropriate for dry-cleaning.
- Suitable for the thermo-transfer on impregnated Polyamide/Nylon and all current textiles which are treated with a water-repellent or impregnated finish. The product is also appropriate for the transfer to Polyester and Polyester/Acrylic textiles.

We recommend evaluation-tests on original material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability of course can only cover the unprocessed material.

Standard Dimensions

500 mm x 25 m
1524 mm x 25 m

11.03.2004