

# **SOLVENT-FLOCK PS 5910**

### **Product Information**

SOLVENT-FLOCK PS 5910 is a self-adhesive Viscose Flock (white, 500  $\mu$ ) suitable for direct printing with Eco-solvent and solvent inks. Due to the special fiber impregnation, a photo realistic print resolution with radiant colours is achieved.

SOLVENT-FLOCK PS 5910 can be used for a one-time textile application and is removable residue-free afterwards.

The liner on the hotmelt side allows motifs and logos to be cut by all current CAD/CAM plotters after printing. The Flock has excellent cutting and weeding abilities.

SOLVENT-FLOCK PS 5910 is not suitable for heat transfer.

#### We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

#### Standard Dimensions

500 mm x 25 m

1.000 mm x 25 m

500 mm x 50 m

#### **Technical Data**

Transfer Film: Viscose Flock, self-adhesive

Adhesive: Acrylic adhesive

Thickness [mm]: 0,50 + /-5%

Liner: Silicone-paper, white

#### Wash Resistance

Wash resistance: Not washable.

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37 E-Mail: info@poli-tape.de Internet: www.poli-tape.de 11/03/2014

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.