



DATA SHEET PAPER TAPE HEX 100 HIGH TACK

Stabilised 110-micron paper, coated with a pressure sensitive rubber adhesive. Intended for making and installing decal kits (logos, cut letters smaller than 5cm/2in...).

CHARACTERISTICS OF THE FILM:

	<u>Average values</u>
• Thickness (µm):	110
• Tensile strength (N/25mm):	92
• Elongation at break (%):	14

ADHESIVE PROPERTIES:

• Adhesion (N/25mm)	4
---------------------	---

RECOMMENDATIONS:

- Minimum installation temperature: +15°C (+59°F)
- Exposure temperature range: +15°C to +35°C (+59°F to +95°F)
- Tape for use with applications that require good stability over time (dimensional and for long term storage) and resistance to humidity.
- Good adhesion on the liner: reduced folds, tunnels and peel of the edges.

ADHESIVE:

- Natural rubber based

STORAGE:

- Shelf life (before application):
1 year if stored unopened in its original packing at a temperature of 21°C (70°F) and 50% relative humidity.

Note:

Because of the great variety of substrates and possible application methods the installer must examine the suitability of the media for each application. The methods of measuring for the standards quoted above are the basis for the development of our own measuring methods which are available on request (partial application). You are invited to enquire for the latest instructions in force.

All published data are based on measurements carried out regularly under laboratory conditions. They do, however, not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The seller assumes no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: www.hexisgroup.com.