

## Product Information

Application Tape based on a one-sided embossed, transparent, dimensionally stable polyethylene film. Ideally suitable for transferring of all cast and calendered PVC CAD/CAM films.

Especially to be emphasised are the following properties:

- The film has a high tensile strength which ensures an exact positioning of all letters. The excellent flatness assists the easy application.
- The acrylic adhesive is specially developed and has a constant high adhesive strength level. It can be removed without residues, even after a long period of application.
- Can be used for dry and wet application.
- Due to the embossed surface, the film unwinds easily. Static charging of the rolls is prevented.

## Technical Data

<b>Carrier:</b>	HDPE film, pyramid surface	
<b>Adhesive:</b>	Acrylic modified	
<b>Adhesion [N/cm]:</b>	1,40	+/- 10 %
<b>Thickness [mm]:</b>	0,13	+/- 5 %

## Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.